



YY2214253 | Joint torique (2-251), PTFE



Accessories for filter holders for sample preparation.

YY2214253

1

Le prix n'a pas pu être récupéré

La quantité minimale doit être un multiple de

Les prix peuvent être modifiés sans préavis

Aperçu Produits & Applications associés

Aperçu

Description
Informations produit
Applications
Informations sur les matériaux
Informations sur l'emballage

Description	
Référence	YY2214253
Description	Joint torique (2-251), PTFE

Description	
Informations générales	Do your waste samples contain volatile substances, such as isopropanol, acetone or xylene? Then use our ZHE (Zero Head Space Extractor) Hazardous Waste Filtration system, which is approved by the US Environmental Protection Agency (EPA) as an apparatus for Toxicity Characteristic Leaching Procedure (TCLP) measurement. The system cannot pressurize unless completely assembled; this eliminates accidentally "shooting the piston" out of the unit and assures safe operation. Choose both manual and automatic venting modes. Features & Benefits: •Allows for pressurization of filter without introducing air, due to movable piston design •Prevents loss of volatiles •Manual and automatic venting modes •System cannot be pressurized unless completely assembled, thereby preventing "shooting the piston" out of the unit accidentally Applications: US EPA Extraction Procedure (EP) Toxicity Test and Toxicity Characteristic Leaching Procedure Hazardous Waste System YT30090HW Millipore ZHE Hazardous Waste System Replacement Parts XX2702512 2-way Valve, 1/8 in. NPTM, stainless steel XX6700010 Cylinder O-rings 3 XX6700024 Vent/Relief Valve, 9 bar XX6700104 Street Elbow, 1/4 in. NPTF to M YT3009001 Piston with O-rings, wiper seal YT3009002 Fitting Luer 1/8 in. NPTF YT3009003 Piston O-rings, wiper seal YT3009013 Quick-disconnect Female Swagelok YT3009014 Quick-disconnect Male Swagelok YY2209064 Support Screen 90 mm, stainless steel YY2209068 O-ring, 2-235, 90 mm, fluoroelastomer YY2214257 Hand Knob Accessories XX6700P05 Dispensing Pressure Vessel, 5 L YT3009015 ZHE Tight Syringe, 50ml YT3009016 ZHE Tedlar Bag, 1 liter Connector Kit Components XX3002567 Adapter, 1/8 in. NPTF to M Luer-Lok, chrome plated XX6700024 Vent/Relief Valve, 9 bar XX6700030 Quick-release Nipple & Coupling, 1/4 in. NPTM XX6700125 Hex Nipple, 1/4 in. NPTM 51 mm., stainless steel XX6702507 Tube Adapter, 1/4 in. NPTM to 1/4 in. Tube XX6702508 Tubing, 6 mm O.D. x 3 m, polypropylene YT3009013 Quick-disconnect Female Swagelok YY1301015 Pressure Gauge, 0–7 bar YY2029348 Ball Valve, 1/4 in. NPTF, stainless steel

Informations produit	
Dispositifs compatibles	• Hazardous Waste System, 142mm

Applications	
Application	Accessories for filter holders for sample preparation.

Informations sur les matériaux	
Chimie	• Polytetrafluoroethylene (PTFE)

Informations sur l'emballage	
Quantité	1

© 2018 Merck KGaA, Darmstadt, Allemagne et/ou ses filiales. Tous droits réservés.

© Merck KGaA, Darmstadt, Allemagne, 2014. Toutes les références à Merck désignent Merck KGaA, Darmstadt, Allemagne.