

Product name : Micrewtube®	Catalogue no.: T332-4S
Edition date : 2005-10-08	Revision date: 2013-09-05
Approved by : Annette Roy, QA coordinator	
<i>This document replaces any previous version</i>	

Product identification

- Designation: **1.5 Micrewtube® with screw cap**

Production Information

- Producer's name: **Simport Scientific**
➤ Address: 2588 Bernard Pilon, Beloeil (Québec), J3G 4S5
➤ Tel. no / web site: (450) 464-1723 / www.Simport.com

Packaging

- Case Cardboard box with 10 packs of 50 units, for a total of 500 units

Traceability.

- Lot no
➤ Composition: 8 digits
➤ Location: ① On exterior case label.
(The lot number can be found in different locations) ② On inserted label inside case.
③ On inner package.

Standard conformity.

- **MIL-STD-105E** Sampling and inspection procedures
➤ **FDA** Resin Conforms to FDA 21 CFR 177.1520
➤ **USP** Resin conforms to USP Class VI
➤ **Coneg** Plastics and colorants are in conformity with CONEG standards
➤ **Rohs** Plastics and colorants are in conformity with Rohs standards

Quality assurance

- No presence of contamination in plastic
- Visual attributes
- Dimension measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm/Hg
- Liquid nitrogen resistance testing (gas phase only)

Specifications

- Disposable, non-printed, skirted 1.5ml Micrewtube with oring seal and attachment loop cap
- Sterilized by gamma radiation, with pre-assembled and screwed on caps
- Certified DNase, RNase and DNA free
- Material: polypropylene for tube and cap
- Silicone for seal
- Centrifugation resistant at 17 000 g
- Autoclavable at 121 °C, for up to 30 minutes.
- Temperature range: -196°C to 121 °C

Storage conditions

- Store in cool dry place.
- Avoid temperature variations and humidity.
- Protect from any possible contamination.
- Protect from any damage to the packaging, which could compromise sterility

Recommended use

- Check cap closure when using biohazard material and/or chemical reagents.
- Follow chemical resistance chart recommendations
- Follow manufacturers instruction for automated equipment
- Should be used only in gas phase of liquid nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are copyrighted and are protected by



Product name : **Micrewtube®**

Catalogue no.: **T332-4S**

worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way