

Product name : Micrewtube®	Catalogue no.: T334-2S
Edition date : 2005-10-08 Approved by : Annette Roy, QA coordinator	Revision date: 2014-05-01
<i>This document replaces any previous version</i>	

↻ **Product identification**

- Designation: **Micrewtube® with screw cap**

↻ **Production Information**

- Producer's name: **Simport Scientific**
- Address: 2588 Bernard Pilon, Beloeil (Québec), J3G 4S5
- Tel. no / web site: (450) 464-1723 / www.Simport.com

↻ **Packaging**

- Case Cardboard box containing 10 bags of 50 units

↻ **Traceability.**

- Lot no
 - ➔ Composition: 8 digits
 - ➔ Location:
 - ① On exterior case label.
 - ② On inserted label inside case.
 - ③ On inner package.

(The lot number can be found in different locations)

↻ **Standard conformity.**

- **MIL-STD-105E** Sampling and inspection procedures
- **FDA** Resin Conforms to FDA 21 CFR 177.1520
- **USP** Resin conforms to USP Class VI
- **Coneg** Plastics and colorants are in conformity with CONEG standards
- **Rohs** Plastics and colorants are in conformity with Rohs standards

[↻](#) **Quality assurance**

- Clear, no presence of contamination in plastic
- Visual attributes
- Dimensions and volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm/Hg
- Liquid nitrogen resistance testing (gas phase only)

[↻](#) **Specifications**

- Disposable 0.5ml Micrewtube, Self-standing, Non-printed assembled screw cap with washer seal
- Sterilized by gamma radiation, with pre-assembled and screwed on caps
- Certified DNase, RNase DNA and pyrogen free
- Material: polypropylene for tube and cap
- Silicone for washer seal
- Autoclavable at 121 °C, for up to 30 minutes.
- Temperature range: -196 °C to 121 °C

[↻](#) **Storage conditions**

- Store in cool dry place.
- Avoid temperature variations and humidity.
- Protect from any possible contamination.
- Protect from any damage to the packaging, which could compromise sterility

[↻](#) **Recommended use**

- Check cap closure when using biohazard material and/or chemical reagents.
- Follow chemical resistance chart recommendations
- Follow manufacturers instruction for automated equipment
- Should be used only in gas phase of liquid nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way