

L A N D A N G E R	FICHE TECHNIQUE PRODUIT PRODUCT TECHNICAL SHEET	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-------------------	--	--

Editée le / Publishing date

2022-04-29

Page

1

REFERENCE	DESIGNATIONS - DESCRIPTIONS	CODE EAN
D037066	PINCE TUBULAIRE L:96MM 9X2MM COURBE DROITE DE HEERMANN	3661219400219
	HEERMANN TUBULAR EAR FORCEPS L:96MM 9X2MM CURVED RIGHT	 3 661219 400219

Catalogues / catalogs

ORL 2021

Chapitre-page

161

DESCRIPTIF DU DISPOSITIF/ PRODUCT DESCRIPTION

L A N D A N G E R

Micro pinces - Micro forceps - Micro pinzas

Mors lisses
Smooth jaws
Bocas lisas

75 mm

D035043 0,8 x 4,5 mm
D035047 1 x 6 mm



D035043
13 cm - 5"

Mors lisses
Smooth jaws
Bocas lisas

L

7 x 1,0 mm L : 70 mm

D037060 Droite / Straight / Recta
D037061 Courbe droite / Right curve / Curva derecha
D037062 Courbe gauche / Left curve / Curva izquierda

9 x 2,0 mm L : 90 mm

D037065 Droite / Straight / Recta
D037066 Courbe droite / Right curve / Curva derecha
D037067 Courbe gauche / Left curve / Curva izquierda



D037060
13 cm - 5"

Copyright © LANDANGER - 2018 - 2021

Vt - Otolaryngologie
Vt - Otolaryngologie
Vt - Otolaryngologie

 1/1

161

LANDANGER	FICHE TECHNIQUE PRODUIT <i>PRODUCT TECHNICAL SHEET</i>	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	---	---

Éditée le / *Publishing date*

2022-04-29

Page

2

REFERENCE	DESIGNATIONS - <i>DESCRIPTIONS</i>	CODE EAN
D037066	PINCE TUBULAIRE L:96MM 9X2MM COURBE DROITE DE HEERMANN	3661219400219
	HEERMANN TUBULAR EAR FORCEPS L:96MM 9X2MM CURVED RIGHT	 3 661219 400219

INFORMATIONS REGLEMENTAIRES / *REGULATORY INFORMATION*

Classe CE :
CE Class :

I

Code GMDN :
GMDN code :

62468

PERFORMANCES REVENDIQUEES / *INTENDED PERFORMANCE*

Dispositif médical de bloc opératoire :
Operating room medical device :

REUTILISABLE/REUSABLE

CARACTERISTIQUES SPECIFIQUE / *SPECIFIC FEATURES*

Type matière :
Material type :

ACIER INOXYDABLE / STAINLESS STEEL

Nuance matière :
Material grade :

X20Cr13(1.4021) + X5CrNi18-10(1.4301) + X8CrNiS18-9(1.4305) + X10CrNi18-8(1.4310)

Dimensions : Voir désignations produits
Outer dimensions : See products description
Chapitre-pages

ORL 2021

161

Nettoyage/Pré-désinfection : Standard pour instrumentation de bloc opératoire réutilisable.
Cleaning / Pre-disinfection : Standard conditions for reusable surgical instruments

Stérilisation :

La stérilisation doit être effectuée selon un procédé de stérilisation à la vapeur conformément à la norme ISO 17665-1 (procédé sous vide fractionné) avec un stérilisateur conformément à la norme EN 285.

Méthode de stérilisation à la vapeur saturée	Température	Durée	Temps de séchage	Pression absolue
Pré-vide	132 °C (270 °F)	4 minutes	30 minutes	2,9 bars, 2,8 atm, 41,6 psi
Pré-vide	134 °C (273 °F)	3 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	5 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	18 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi

Sterilization process :

The Sterilization shall be performed according to ISO 17665-1 validated steam sterilisation procedure (fractional vacuum procedure) in an autoclave in compliance with EN 285.

Saturated steam sterilization method	Temperature	Time	Drying time	Absolute pressure
Pre-vacuum	132 °C (270 °F)	4 minutes	30 minutes	2.9 bar, 2.8 atm, 41.6 psi
Pre-vacuum	134 °C (273 °F)	3 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	5 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	18 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi

EMBALLAGE / *PACKAGING*

Conditionnement : Pochette plastique en polyéthylène (PE).
Packaging : Polyethylene plastic pouch (PE).