

LANDANGER	FICHE TECHNIQUE PRODUIT PRODUCT TECHNICAL SHEET	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	--	--

Editée le / Publishing date

2022-04-28

Page

1

REFERENCE	DESIGNATIONS - DESCRIPTIONS	CODE EAN
DC20112-09	MICRO CISEAUX LAMES 9MM L:90MM DROIT TENOTOMIE	3661219293392
	MICRO SCISSORS 9MM BLADE L:90MM ST TENOTOMY	 3 661219 293392

Catalogues / catalogs

Delacroix 2020

Chapitre-page

02-019

DESCRIPTIF DU DISPOSITIF/ PRODUCT DESCRIPTION



Micro Scissors / Micro Ciseaux / Micro Tijeras

10 mm Blades - Round Handle
Lames 10 mm - Manche Rond
Lamas 10 mm - Mango Redondo

Vannas
Tenotomy
Ténotomie
Tenotomía

Straight
Droit
Recta



DC20110-12
L: 120 mm - 4 ³/₄"

DC20110-15 NEW NOUVEAU NUEVO
L: 150 mm - 6"

DC20110-18
L: 180 mm - 7"



Straight
Droit
Recta



DC20112-09
L: 90 mm - 3 ¹/₂"

DC20112-12
L: 120 mm - 4 ³/₄"

DC20112-15 NEW NOUVEAU NUEVO
L: 150 mm - 6"

DC20112-18 NEW NOUVEAU NUEVO
L: 180 mm - 7"

Curved
Courbe
Curva



DC20111-12
L: 120 mm - 4 ³/₄"

DC20111-15 NEW NOUVEAU NUEVO
L: 150 mm - 6"

DC20111-18 NEW NOUVEAU NUEVO
L: 180 mm - 7"



Curved
Courbe
Curva



DC20113-09
L: 90 mm - 3 ¹/₂"

DC20113-12
L: 120 mm - 4 ³/₄"

DC20113-15 NEW NOUVEAU NUEVO
L: 150 mm - 6"

DC20113-18 NEW NOUVEAU NUEVO
L: 180 mm - 7"

 : Add TI for Titanium Model / Ajoutez TI pour le Modèle Titane / Añadir TI para Modelo Titánio


19

LANDANGER	FICHE TECHNIQUE PRODUIT <i>PRODUCT TECHNICAL SHEET</i>	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	---	---

Éditée le / *Publishing date*

2022-04-28

Page

2

REFERENCE	DESIGNATIONS - <i>DESCRIPTIONS</i>	CODE EAN
DC20112-09	MICRO CISEAUX LAMES 9MM L:90MM DROIT TENOTOMIE	3661219293392
	MICRO SCISSORS 9MM BLADE L:90MM ST TENOTOMY	 3 661219 293392

INFORMATIONS REGLEMENTAIRES / *REGULATORY INFORMATION*

Classe CE :
CE Class :

I

Code GMDN :
GMDN code :

38727

PERFORMANCES REVENDIQUEES / *INTENDED PERFORMANCE*

Dispositif médical de bloc opératoire :
Operating room medical device :

REUTILISABLE/REUSABLE

CARACTERISTIQUES SPECIFIQUE / *SPECIFIC FEATURES*

Type matière :
Material type :

ACIER INOXYDABLE / STAINLESS STEEL

Nuance matière :
Material grade :

X46Cr13(1.4034)

Dimensions : Voir désignations produits
Outer dimensions : See products description
Chapitre-pages

Delacroix 2020

02-019

Nettoyage/Pré-désinfection : Standard pour instrumentation de bloc opératoire réutilisable.
Cleaning / Pre-disinfection : Standard conditions for reusable surgical instruments

Stérilisation :

La stérilisation doit être effectuée selon un procédé de stérilisation à la vapeur conformément à la norme ISO 17665-1 (procédé sous vide fractionné) avec un stérilisateur conformément à la norme EN 285.

Méthode de stérilisation à la vapeur saturée	Température	Durée	Temps de séchage	Pression absolue
Pré-vide	132 °C (270 °F)	4 minutes	30 minutes	2,9 bars, 2,8 atm, 41,6 psi
Pré-vide	134 °C (273 °F)	3 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	5 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	18 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi

Sterilization process :

The Sterilization shall be performed according to ISO 17665-1 validated steam sterilisation procedure (fractional vacuum procedure) in an autoclave in compliance with EN 285.

Saturated steam sterilization method	Temperature	Time	Drying time	Absolute pressure
Pre-vacuum	132 °C (270 °F)	4 minutes	30 minutes	2.9 bar, 2.8 atm, 41.6 psi
Pre-vacuum	134 °C (273 °F)	3 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	5 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	18 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi

EMBALLAGE / *PACKAGING*

Conditionnement : Pochette plastique en polyéthylène (PE).
Packaging : Polyethylene plastic pouch (PE).