

LANDANGER	FICHE TECHNIQUE PRODUIT PRODUCT TECHNICAL SHEET	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	--	---

Éditée le / Publishing date

2022-04-28

Page

1

REFERENCE	DESIGNATIONS - DESCRIPTIONS	CODE EAN
DC50013-23	MICRO PORTE AIGUILLE JACOBSON L:225MM MANCHE ROND COURBE I:0.3MM AVEC CREMAILLIERE DIAMONITE	3661219138990
	JACOBSON MICRO N H L:225MM ROUND HANDLE CURVED W:0.3MM W/ RATCHET DIAMONITE	 3 661219 138990

Catalogues / catalogs

Delacroix 2020

Chapitre-page

05-003

DESCRIPTIF DU DISPOSITIF/ PRODUCT DESCRIPTION



Micro Needle Holders / Micro Porte-Aiguilles / Micro Porta Aguja

Width: 0.3 mm - For Suture: 12/0 -> 8/0 - Round Handle
 Largeur: 0.3 mm - Pour Suture: 12/0 -> 8/0 - Manche Rond
 Anchura: 0.3 mm - Para Sutura: 12/0 -> 8/0 - Mango Redondo


Diamonite

Straight - Without Ratchet
Droit - Sans Verrou
Recta - Sin Cerrojo

- DC50020-12
L: 120 mm - 4 3/4"
- DC50020-14
L: 145 mm - 5 3/4"
- DC50021-18 
L: 180 mm - 7"
- DC50022-21 
L: 205 mm - 8"
- DC50023-23
L: 225 mm - 9"
- DC50023-25
L: 250 mm - 10"

Curved - Without Ratchet
Courbe - Sans Verrou
Curva - Sin Cerrojo

- DC50030-12
L: 120 mm - 4 3/4"
- DC50030-14
L: 145 mm - 5 3/4"
- DC50031-18 
L: 180 mm - 7"
- DC50032-21 
L: 205 mm - 8"
- DC50033-23
L: 225 mm - 9"
- DC50033-25
L: 250 mm - 10"

Straight - With Ratchet
Droit - Avec Verrou
Recta - Con Cerrojo

- DC50000-12
L: 120 mm - 4 3/4"
- DC50000-14
L: 145 mm - 5 3/4"
- DC50001-18 
L: 180 mm - 7"
- DC50002-21
L: 205 mm - 8"
- DC50003-23
L: 225 mm - 9"
- DC50003-25
L: 250 mm - 10"

Curved - With Ratchet
Courbe - Avec Verrou
Curva - Con Cerrojo

- DC50010-12
L: 120 mm - 4 3/4"
- DC50010-14
L: 145 mm - 5 3/4"
- DC50011-18
L: 180 mm - 7"
- DC50012-21
L: 205 mm - 8"
- DC50013-23 
L: 225 mm - 9"
- DC50013-25
L: 250 mm - 10"




LANDANGER	FICHE TECHNIQUE PRODUIT <i>PRODUCT TECHNICAL SHEET</i>	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	---	---

Éditée le / *Publishing date*

2022-04-28

Page

2

REFERENCE	DESIGNATIONS - <i>DESCRIPTIONS</i>	CODE EAN
DC50013-23	MICRO PORTE AIGUILLE JACOBSON L:225MM MANCHE ROND COURBE I:0.3MM AVEC CREMAILLERE DIAMONITE	3661219138990
	JACOBSON MICRO N H L:225MM ROUND HANDLE CURVED W:0.3MM W/ RATCHET DIAMONITE	 3 661219 138990

INFORMATIONS REGLEMENTAIRES / *REGULATORY INFORMATION*

Classe CE :
CE Class :

I

Code GMDN :
GMDN code :

12726

PERFORMANCES REVENDIQUEES / *INTENDED PERFORMANCE*

Dispositif médical de bloc opératoire :
Operating room medical device :

REUTILISABLE/REUSABLE

CARACTERISTIQUES SPECIFIQUE / *SPECIFIC FEATURES*

Type matière :
Material type :

ACIER INOXYDABLE + TUNGSTENE / STAINLESS STEEL + TUNGSTEN

Nuance matière :
Material grade :

X20Cr13(1.4021) + TUNGSTENE

Dimensions : Voir désignations produits
Outer dimensions : See products description
Chapitre-pages

Delacroix 2020

05-003

Nettoyage/Pré-désinfection : Standard pour instrumentation de bloc opératoire réutilisable.
Cleaning / Pre-disinfection : Standard conditions for reusable surgical instruments

Sterilisation :

La stérilisation doit être effectuée selon un procédé de stérilisation à la vapeur conformément à la norme ISO 17665-1 (procédé sous vide fractionné) avec un stérilisateur conformément à la norme EN 285.

Méthode de stérilisation à la vapeur saturée	Température	Durée	Temps de séchage	Pression absolue
Pré-vide	132 °C (270 °F)	4 minutes	30 minutes	2,9 bars, 2,8 atm, 41,6 psi
Pré-vide	134 °C (273 °F)	3 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	5 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	18 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi

Sterilization process :

The Sterilization shall be performed according to ISO 17665-1 validated steam sterilisation procedure (fractional vacuum procedure) in an autoclave in compliance with EN 285.

Saturated steam sterilization method	Temperature	Time	Drying time	Absolute pressure
Pre-vacuum	132 °C (270 °F)	4 minutes	30 minutes	2.9 bar, 2.8 atm, 41.6 psi
Pre-vacuum	134 °C (273 °F)	3 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	5 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	18 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi

EMBALLAGE / *PACKAGING*

Conditionnement : Pochette plastique en polyéthylène (PE).
Packaging : Polyethylene plastic pouch (PE).