

LANDANGER	FICHE TECHNIQUE PRODUIT PRODUCT TECHNICAL SHEET	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	--	---

Éditée le / Publishing date

2022-04-28

Page

1

REFERENCE	DESIGNATIONS - DESCRIPTIONS	CODE EAN
DC50432-21	MICRO PORTE AIGUILLE JACOBSON L:215MM MANCHE PLAT COURBE I:1.2MM SANS CREMAILLE TUNGSTENE	3661219140306
	JACOBSON MICRO N H L:215MM FLAT HANDLE CURVED W:1.2MM W/O RATCHET TC	 3 661219 140306

Catalogues / catalogs

Delacroix 2020

Chapitre-page

05-020

DESCRIPTIF DU DISPOSITIF/ PRODUCT DESCRIPTION




Micro Needle Holders / Micro Porte-Aiguilles / Micro Porta Agujas

Smooth Jaws - Width: 1,2 mm - For Suture: 7/0 -> 5/0 - Flat Handle
Mors Lisses - Largeur: 1,2 mm - Pour Suture: 7/0 -> 5/0 - Manche Plat
Bocas Lisas - Anchura: 1,2 mm - Para Sutura: 7/0 -> 5/0 - Mango Plano



TC Inserts



Straight - Without Ratchet
Droit - Sans Verrou
Recta - Sin Cerrojo

DC50410-14
L: 145 mm - 5 3/4"

DC50411-18
L: 180 mm - 7"

DC50412-21
L: 215 mm - 8 1/2"

DC50412-23
L: 230 mm - 9"

DC50412-25
L: 245 mm - 10"



Straight - With Ratchet
Droit - Avec Verrou
Recta - Con Cerrojo

DC50400-14
L: 145 mm - 5 3/4"

 DC50401-18
L: 180 mm - 7"

DC50402-21
L: 215 mm - 8 1/2"

DC50402-23
L: 230 mm - 9"

DC50402-25
L: 245 mm - 10"



Curved - Without Ratchet
Courbe - Sans Verrou
Curva - Sin Cerrojo

DC50430-14
L: 145 mm - 5 3/4"

 DC50431-18
L: 180 mm - 7"

DC50432-21
L: 215 mm - 8 1/2"

DC50432-23
L: 230 mm - 9"

DC50432-25
L: 245 mm - 10"



Curved - With Ratchet
Courbe - Avec Verrou
Curva - Con Cerrojo

DC50420-14
L: 145 mm - 5 3/4"

DC50421-18
L: 180 mm - 7"

DC50422-21
L: 215 mm - 8 1/2"

DC50422-23
L: 230 mm - 9"

DC50422-25
L: 245 mm - 10"

5 - Suture

20

Copyright LANDANGER - 2009 - 2020

LANDANGER	FICHE TECHNIQUE PRODUIT <i>PRODUCT TECHNICAL SHEET</i>	FAQ 026 INFO Indice : 2 Date : 01/06/2018
-----------	---	---

Éditée le / *Publishing date*

2022-04-28

Page

2

REFERENCE	DESIGNATIONS - <i>DESCRIPTIONS</i>	CODE EAN
DC50432-21	MICRO PORTE AIGUILLE JACOBSON L:215MM MANCHE PLAT COURBE I:1.2MM SANS CREMAILLE TUNGSTENE	3661219140306
	JACOBSON MICRO N H L:215MM FLAT HANDLE CURVED W:1.2MM W/O RATCHET TC	 3 661219 140306

INFORMATIONS REGLEMENTAIRES / *REGULATORY INFORMATION*

Classe CE :

I

Code GMDN :

12726

CE Class :

GMDN code :

PERFORMANCES REVENDIQUEES / *INTENDED PERFORMANCE*

Dispositif médical de bloc opératoire :

REUTILISABLE/REUSABLE

Operating room medical device :

CARACTERISTIQUES SPECIFIQUE / *SPECIFIC FEATURES*

Type matière :

ACIER INOXYDABLE + TUNGSTENE / STAINLESS STEEL + TUNGSTEN

Material type :

Nuance matière :

X20Cr13(1.4021) + TUNGSTENE

Material grade :

Dimensions :

Voir désignations produits

Delacroix 2020

Outer dimensions :

See products description

Chapitre-pages

05-020

Nettoyage/Pré-désinfection : Standard pour instrumentation de bloc opératoire réutilisable.

Cleaning / Pre-disinfection : *Standard conditions for reusable surgical instruments*

Stérilisation :

La stérilisation doit être effectuée selon un procédé de stérilisation à la vapeur conformément à la norme ISO 17665-1 (procédé sous vide fractionné) avec un stérilisateur conformément à la norme EN 285.

Méthode de stérilisation à la vapeur saturée	Température	Durée	Temps de séchage	Pression absolue
Pré-vide	132 °C (270 °F)	4 minutes	30 minutes	2,9 bars, 2,8 atm, 41,6 psi
Pré-vide	134 °C (273 °F)	3 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	5 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi
Pré-vide	134 °C (273 °F)	18 minutes	35 minutes	3,0 bars, 3,0 atm, 44,1 psi

Sterilization process :

The Sterilization shall be performed according to ISO 17665-1 validated steam sterilisation procedure (fractional vacuum procedure) in an autoclave in compliance with EN 285.

Saturated steam sterilization method	Temperature	Time	Drying time	Absolute pressure
Pre-vacuum	132 °C (270 °F)	4 minutes	30 minutes	2.9 bar, 2.8 atm, 41.6 psi
Pre-vacuum	134 °C (273 °F)	3 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	5 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi
Pre-vacuum	134 °C (273 °F)	18 minutes	35 minutes	3.0 bar, 3.0 atm, 44.1 psi

EMBALLAGE / *PACKAGING*

Conditionnement :

Pochette plastique en polyéthylène (PE).

Packaging :

Polyethylene plastic pouch (PE).